sferaco
VALVES, METERS & FITTINGS

ISO 9001 : 2015
BUREAU VERITAS
Certification

REF. 328

BRASS SPRING CHECK VALVE NYLON DISC MALE MALE BSP ACS 4MS

Brass spring check valve for drinking water, water distribution, watering and heating.
Brass CW617N-4MS body, POM disc and NBR gasket for an excellent low and high pressure tightness.
Perfect centering of the throttle on the seat thanks to the double axial and lateral guidance
All positions thanks to the stainless steel AISI 302 spring.

ATTESTATION DE CONFORMITÉ SANITAIRE ACS

4MS

Size :	DN3/8" to DN1"
Connection :	Male-male BSP
Min Temperature :	-10°C
Max Temperature :	+110°C
Max Pressure :	16 Bars
Specifications :	All positions AISI 302 spring POM disc NBR gasket Low head loss
Materials :	Brass CW617N-4MS according to EN 12165

Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.fr E-mail : info@sferaco.fr

Information provided as an indication and subject to possible modification

BRASS SPRING CHECK VALVE NYLON DISC MALE MALE BSP ACS 4MS

SPECIFICATIONS :

- Respect the flow direction indicated by the arrow
- BSP cylindrical threaded ends
- POM throttle
- Perfect centering of the throttle on the seat thanks to the double axial and lateral guidance
- Low opening pressure
- Better mechanical strength thanks to the brass CW617N-4MS body
- All positions with AISI 302 spring
- Excellent low and high pressure tightness thanks to the NBR gasket

USE :

- Heating, drinkable water, cold and hot water
- Min Temperature Ts : - 10°C
- MaxTemperature Ts :+ 110°C
- Max Pressure Ps : 16 bars

HEAD LOSS GRAPH :



Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.fr E-mail : info@sferaco.fr

Information provided as an indication and subject to possible modification

BRASS SPRING CHECK VALVE NYLON DISC MALE MALE BSP ACS 4MS

OPENING PRESSURE :

- Opening pressure between 20 and 200 mbar

RANGE :

- Brass spring check valve male – male BSP type from DN3/8" to DN1" **Ref. 328**

MATERIALS :



Item	Designation	Materials
1	Body	Brass CW617N-4MS according to EN 12165
2	Spring	AISI 302
3	Throttle	POM
4	Gasket	NBR
5	Bonnet	Brass CW617N-4MS according to EN 12165

Information provided as an indication and subject to possible modification

BRASS SPRING CHECK VALVE NYLON DISC MALE MALE BSP ACS 4MS

SIZE (in mm) :



DN	3/8"	1/2"	3/4"	1"
Ø A	27	29	37	45
L	56	56	63	70
L1	9	10	11	11
Weight (in Kg)	0.1	0.11	0.19	0.29
Ref.	328003	328004	328005	328006

STANDARDS :

- Manufacturer certified ISO 9001 :2015
- DIRECTIVE 2014/68/EU : Products excluded from directive (Article 4, § 3)
- French water agreement **A.C.S. N° 25 ACC LY 624**
- Threaded male BSP cylindrical ends according to ISO 228-1

ADVICE : Our opinion and our advice are not guaranteed and SFERACO shall not be liable for the consequences of damages.
The customer must check the right choice of the products with the real service conditions.

Sferaco 90 rue du Ruisseau 38297 St Quentin Fallavier Tel: + 33 (0) 474.94.15.90 Fax: + 33 (0) 474.95.62.08 Internet: www.sferaco.fr E-mail : info@sferaco.fr

Information provided as an indication and subject to possible modification